

## **Structural Performance** Certification **Authorization Report**

Doc No:		FRI	l B1-	02	
Rev No:	7	Page:	1	Of:	1

Required By

PRO B1-03

CAR & Product ID Number: 757 - 103.0

> Issue Date: 7/8/2013 Revision Date: 3/19/2019 **Expiration Date:** 4/7/2024 Company Code: 757

This Certification Authorization Report (CAR) is issued by Keystone Certifications, Inc. (KCI) after full validation review, and is based on a standardized evaluation of the product conducted by an independent accredited laboratory in accordance with the specified referenced standard. Actual fenestration product performance may vary based on many factors, including installation, condition of the wall/roof substrate and the age of the product and installation components.

This report indicates the product is eligible for the application of Keystone Certification Program certification labels. Licensee stipulates in affixing certification labels to products, that those products are representative of the specimen evaluated and documented for certification authorization. Only products bearing such a certification label shall be considered certified. The information in this report can be verified at www.keystonecerts.com.

Licensee Information:	Product Information:
Pocahontas Aluminum Company, Inc.	Model: SS46 PVC Single Slider XO
2001 Industrial Drive, PO Box 756	Operator Type: HS
Pocahontas, AR 72455	Config: EM/IM
USA	Max Width: 72
	Max Height: 48

Referenced Standard:	Product Rating:	
AAMA/WDMA/CSA 101/I.S.2/A440-08	Class R-PG30 1816x1207 (72x48)-Type HS	

Qualifying Test Information:		
Test Report No:	ATI-A9078.06-501-47	
Test Report Expiration:	4/7/2024	

## **Authorized Signature:**

Dennis Fassnacht Jr. Veir Jul Jo 2019.03.19 13:59:35

**Keystone Certifications, Inc.** 

145 Limekiln Rd. Suite 100B New Cumberland, Pennsylvania 17070

Phone: 717-932-8500 Fax: 717-932-8501

## **INSTALLATION METHOD PVC (VINYL) SS46 SINGLE SLIDER WINDOW ELEVATION & ANCHOR LAYOUT** 71-1/2" MAX WIDTH 471/2" MAX HEIGHT 1" FROM CORNERS TYP TOP & BOTTOM-1"FROM CORNERS TYP 8-1/2" MAX TYP INSTALLATION ANCHOR 8-1/2 " TYP TOP & BOTTOM 8" TYPICAL 2" MAX FROM CORNER MEASUREMENT 2 x Buck -**CAULK BETWEEN FLANGE & STRUCTURE** (By Others) #8 - 2" Truss Head Screw (By Others) 8" TYPICAL MIN. EDGE DISTANCE 9/16' **Mounting Flang** <del>/</del>1.50"<del>/</del> 1.50" MIN. PENETRATION **REVISIONS** SCALE: NTS COPYING OR INSTALLATION METHOD **DUPLICATION IS** PVC (VINYL) SS46 SINGLE SLIDER WINDOW ELEVATION & ANCHOR LAYOUT NO. DESCRIPTION ВΥ DATE **DWN BY: AMM** PROHIBITED WITHOUT WRITTEN PREMISSION PREPARED BY: FROM POCAHONTAS CHK BY: KEA POCAHONTAS ALUMINUM COMPANY, INC. ALUMINUM 2001 INDUSTRIAL DRIVE COMPANY, INC. DATE: 10/13/15 POCAHONTAS, AR 72455 PH: 870-892-3689 FAX: 870-892-9858