



PAC
SINCE 1963
An Employee Owned Company

100HZ
Horizontal Slider
1-1/2" Frame Depth

100HZ SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft ² -°F)	CR	STC/ OITC*
Horizontal Slider	WZ3@48psf	46 x 27	48	2.92	<0.50	n/a	n/a	n/a

PAC's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

STANDARD FEATURES:

- Material: Non-Thermal Aluminum
- Frame Depth: 1-1/2"
- Standard Infill Options: Single & Double Strength
- Min Size:
 - 24" x 24"
- Max Size:
 - 72" x 48"
- Latching: Spring Loaded Aluminum Latches
- Removable Screen
- Grid Options: Available

FRAME TYPE(S):

- Flush Mount
- Lap Mount

WHY PAC?

- Single point of contact
- On-site training available upon request
- Customizable stocking program

COLOR OPTIONS:



SPECIFICATIONS:

- AAMA 1701.2-12
- 24 CFR 3280.403/305

