



PAC
SINCE 1963
An Employee Owned Company

DD 100

Delta Door
2" Frame Depth

DD 100 SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @ 1.57 psf)	U-Factor* (btu/h-ft ² -°F)
French Doors	+15/-15	74 x 81	15	0.00	0.31	n/a
Side-Hinged	+75/-22	61 x 81	75/22	0.00	<0.10	n/a

PAC's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

STANDARD FEATURES:

- Frame Depth: 2"
- Dual bulb vinyl weather seals
- Glass Configurations: 9-Lite
- Frame: Welded mitered corners
- Panel: Mitered, screw assembly
- Max height: 80"
- Standard Widths: 3', 4', & 5' singles; and 6' doubles

STANDARD HARDWARE:

- Door Knob & Strike
- Deadbolt
- RV Lock (Black or Chrome)
- Safety Chain

WHY PAC?

- Single point of contact
- On-site training available upon request
- Customizable stocking program

COLOR OPTIONS:



SPECIFICATIONS:

- ASTM E289-19
- E547-16
- E330 M-21

GLASS CONFIGURATIONS:

