



PAC
SINCE 1963
An Employee Owned Company

PD 10

Sliding Glass Door
4-3/8" Frame Depth

PD 10 SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft ² -°F)
SGD	WZ 3 @ 58psf	72 x 76	58	5.43	<0.30	.28

**Performance varies based on glass selection, contact PAC for project specific performance. U-Factor based on 3/4" IGU with soft-coat low-e and argon.*

PAC's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

STANDARD FEATURES:

- Material: uPVC
- Configuration: OX & OXO
- Frame Depth: 4-3/8"
- Standard Infill Options: 3/4" & 5/8" IG
- Pre-punched Integral Nail Fin
- Integral J-Channel

STANDARD HARDWARE:

- Pull-handle with thumb-latch
- Weather resistant tandem rollers

COLOR OPTIONS:



White



Clay

SPECIFICATIONS:

- AAMA 1701.2-12/CFR 3280.305
- AAMA/WDMA/CSA 101/I.S.2/A440-11
- NFRC 100/200/500

WHY PAC?

- Single point of contact
- On-site training available upon request
- Customizable stocking program

