



PAC
SINCE 1963
An Employee Owned Company

V21

Horizontal Slider
2-5/8" Frame Depth

V21 SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft ² -°F)	CR	STC/ OITC*
Horizontal Slider	R-15	72 x 60	15	4.6	<0.30	0.29	61	n/a

**Performance varies based on glass selection, contact PAC for project specific performance. U-Factor based on 5/8" IGU with soft-coat low-e and argon.*

PAC's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

STANDARD FEATURES:

- Material: uPVC
- Frame Depth: 2-5/8"
- Standard Infill Options: 5/8" IG
- Min Size:
 - 14" x 21"
- Max Size:
 - 72" x 60"
- Integral Nail Fin
- Integral J-channel
- Grid options available
- Configurations:
 - OX, XO, OXO

STANDARD HARDWARE:

- Cam lock w/ keeper

WHY PAC?

- Single point of contact
- On-site training available upon request
- Customizable stocking program

SPECIFICATIONS:

- AAMA 1701.2-12
- 24 CFR 3280.403/305
- NFRC 100/200/500

COLOR OPTIONS:



Tan



White

