



**PAC**  
SINCE 1963  
An Employee Owned Company

**V21**

Single Hung  
2-5/8" Frame Depth

## V21 SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft <sup>2</sup> -°F)	CR	STC/ OITC*
Single Hung	WZ3@58psf	36 x 68	58	2.92	<0.10	0.30	60	n/a

\*Performance varies based on glass selection, contact PAC for project specific performance. U-Factor based on 5/8" IGU with soft-coat low-e and argon.

PAC's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

### STANDARD FEATURES:

- Material: uPVC
- Frame Depth: 2-5/8"
- Standard Infill Options: 5/8"
- Min Size:
  - 14" x 21"
- Max Size:
  - 48" x 72"

### ACCESSORIES:

- Exterior frame bevel
- Tilt sash
- Reinforced lock/keeper rail
- Dual weather stripping

### SPECIFICATIONS:

- AAMA 1701.2-17
- AAMA 1704-17
- 24 CFR 3280.403/305
- NFRC 100/200/500

### WHY PAC?

- Single point of contact
- On-site training available upon request
- Customizable stocking program

