












PAC
SINCE 1963
An Employee Owned Company

V46
Picture Window
3" Frame Depth

V46 SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft ² -°F)	CR or CRF	STC/ OITC*
								
Picture	R-50	60 x 84	50	7.52	<0.10	n/a	n/a	n/a

*Performance varies based on glass selection, contact PAC for project specific performance. U-Factor based on 3/4" IGU with soft-coat low-e and argon.

PAC's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

STANDARD FEATURES:

- Material: uPVC
- Frame Depth: 3"
- Standard Infill Options: 3/4" IG
- Min Size:
 - 14" x 14"
- Max Size:
 - 48" x 73"

INSTALLATION:

- Integral Nail Fin (1-1/8" setback)
- Optional J-channel & Brickmold

COLOR OPTIONS:



SPECIFICATIONS:

- AAMA/WDMA/CSA 101/IS2/A440-08

WHY PAC?

- Single point of contact
- On-site training available upon request
- Customizable stocking program

