



**PAC**  
SINCE 1963  
An Employee Owned Company

**V46**  
Single Hung  
3" Frame Depth

## V46 SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft <sup>2</sup> -°F)	CR	STC/ OITC*
Single Hung	R-45	40 x 63	45	6.90	<0.30	n/a	n/a	n/a

\*Performance varies based on glass selection, contact PAC for project specific performance. U-Factor based on 3/4" IGU with soft-coat low-e and argon.

PAC's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

### STANDARD FEATURES:

- Material: uPVC
- Frame Depth: 3"
- Standard Infill Options: 3/4"
- Min Size:
  - 14" x 21"
- Max Size:
  - 48" x 72"
- Tilt-sash for easy cleaning

### INSTALLATION:

- Integral Nail Fin (1-1/8" setback)
- Optional J-channel & Brickmold

### COLOR OPTIONS:



White

### SPECIFICATIONS:

- AAMA/WDMA/CSA 101/IS2/A440-08

### WHY PAC?

- Single point of contact
- On-site training available upon request
- Customizable stocking program

